

MASONRY SAW



Features	Benefits
Stay level blade guard	Good protection and material viability
Conveyor cart with non slip rubber and tilt-lock wheels	Accurate and stable cut
Water return channels	Dry and clean area improving user's comfort
Fully protected blade support shaft	User's safety and bearings protection
Spring-loaded cutting head actioned by foot pedal or cutting handle	Shock-free cutting, good pressure control so better cutting quality
Crank controlled cutting depth adjustment and head locking device	Accurate cutting depth adjustment and straight through cutting

4.0kW

Ø 500



500mm

190kg

400V 3~
or
Petrol

BBL *Major*
4.0 kW

Part No. BBL-500-415V

Diamond blade for illustration purpose only.

Technical datas	BBL Block Saw
Diamond Blade Diam.	Ø500mm * Available in Ø350mm
Supply Voltage / Power kW	415V / 4.0kW
Generator	11 kVA
Max. blade x bore	Ø 500 x 25.4mm
Tilting head	none
Max cutting depth	195mm
Max cutting length	500mm
Table size	550 x 420mm
Tool speed RPM	2800 min ⁻¹
Hand Arm Vibrations (hourly limit)	<2.5 m/s ²
Sound power / pressure level	97 dB (A) / 81 dB (A)
Dimensions (LxWxH)	1480x610x1550mm
Weight	190kg



Optional Accessory

clipper®